
loggers Documentation

Release 0.1.4

Jonatan Dellagostin

Oct 02, 2018

Contents

1	loggers	3
1.1	Example	3
1.2	Installation	4
1.3	Documentation	4
1.4	Source Code	4
1.5	License	4
2	loggers package contents:	5
2.1	loggers package	5
3	Indices and tables	7
	Python Module Index	9

loggers is a Python library that provides usefull wrapper methods for logging class. To be used as a superclass for your own classes.

1.1 Example

```
>>> from loggers import Loggers
>>>
>>> class spamClass(Loggers):
...     def __init__(self, log_folder=None):
...         super(spamClass, self).__init__('spamClass', log_folder_path=log_folder)
...     def do_stuff(self, arg):
...         if not type(arg) == str:
...             self.log.error("I was expecting a string. :( ")
...         else:
...             self.log.debug("I received my string. :)")
...
>>> spam = spamClass('/tmp/logs/spamClass')
>>> spam.log.error('ERROR')
Log: ERROR | Log level:ERROR | Date:31/10/2016 16:51:47
>>> spam.set_log_rotate_handler(True)
>>> spam.do_stuff(123)
Log: I was expecting a string. :( | Log level:ERROR | Date:31/10/2016 16:51:47
>>> spam.do_stuff('Eggs')
>>> spam.set_log_level('DEBUG')
Log: Changing log level to DEBUG | Log level:DEBUG | Date:31/10/2016 16:51:47
>>> spam.do_stuff('Spam')
Log: I received my string. :) | Log level:DEBUG | Date:31/10/2016 16:51:47
```

1.2 Installation

To install loggers, simply run:

```
$ pip install loggers
```

loggers is compatible with Python 2.6+ and Python 3

1.3 Documentation

<https://loggers.readthedocs.io>

1.4 Source Code

Feel free to fork, evaluate and contribute to this project.

Source: <https://github.com/jonDel/loggers>

1.5 License

GPLv3 licensed.

loggers package contents:

2.1 loggers package

2.1.1 Submodules

2.1.2 loggers.loggers module

class `loggers.loggers.Loggers` (*log_name*, ***kwargs*)

Bases: `object`

Provides log functionalities either in stream or file form

Parameters

- **log_name** (*str*) – name of the log handler
- **log_folder_path** (*str*, optional, *default* =None) – folder where the log’s files will lie
- **log_file** (*str*, optional, *default* =None) – path of the debug and error log’s files
- **logger** (*obj*, optional, *default* =None) – use this preexistent logger instead of creating a new one

set_log_format (*log_type*, *log_format*)

Configures log format

Parameters

- **log_type** (*str*) – log type (error, debug or stream)
- **log_format** (*str*) – log format (ex:”Log: %(message)s | Log level:%(levelname)s | Date:%(asctime)s’,datefmt=’%m/%d/%Y %I:%M:%S”)

set_log_level (*log_level*)

Configures class log level

Parameters **log_level** (*str*) – log level (‘NOTSET’, ‘DEBUG’, ‘INFO’, ‘WARNING’, ‘ERROR’, ‘CRITICAL’)

set_log_rotate_handler (*set_file*)

Enables/disables logs to be written to files

Parameters **set_file** (bool) – False disables, True enables

2.1.3 Module contents

CHAPTER 3

Indices and tables

- `genindex`
- `modindex`
- `search`

I

`loggers`, [6](#)
`loggers.loggers`, [5](#)

L

Loggers (class in `loggers.loggers`), [5](#)

`loggers` (module), [6](#)

`loggers.loggers` (module), [5](#)

S

`set_log_format()` (`loggers.loggers.Loggers` method), [5](#)

`set_log_level()` (`loggers.loggers.Loggers` method), [5](#)

`set_log_rotate_handler()` (`loggers.loggers.Loggers`
method), [5](#)